

RUTX09

NEXT GENERATION LTE CAT6 INDUSTRIAL CELLULAR ROUTER

This powerful LTE router is designed as Main/Backup Internet source where steady connection and high data throughput is required. Equipped with Dual-SIM and 4 x Gigabit Ethernet ports. RUTX09 has all advanced RutOS software and security features.



RELIABLE

Stable 24/7 operation

Connection watchdog

3 alternative internet sources

ROBUST

Durable aluminium housing
Wide voltage range (9-50 V)
External temperature range (-40 +75 °C)


SECURE


Multiple VPN options

Advanced firewall functionality

Various encryption protocols supported







Hardware

Mobile	4G (LTE) – Cat 6 DL up to 300 Mbps, UL up to 50Mbps; DC-HSDPA; HSUPA; WCDMA
CPU	Quad Core ARM Cortex A7 717 MHz CPU
Memory	256 MB Flash, 256 MB DDR3 RAM
Ethernet	4 x 1Gbit Ethernet ports: 1 x WAN (configurable as LAN), 3 x LAN
Power supply	9 - 50 VDC, 4 pin DC connector
PoE (passive)	Passive PoE. Possibility to power up through LAN port, not compatible with IEEE 802.3af and 802.3at standards
Connectors	1 x 4 pin DC, 4 x Ethernet, 2 x Mobile SMA, 1 x GPS SMA
SIM	2 x external SIM holders
Status LEDs	1 x Power, 2 x SIM, 3 x Mobile network type, 5 x Signal Strength
Operating temperature	-40 °C to 75 °C
Housing	Full aluminium with grounding terminal
Dimensions	115 mm x 95 mm x 44 mm
Weight Software	456 g
Operating system	RutOS (OpenWrt based Linux OS)
SIM switch	2 SIM cards, auto-switch cases: data limit, roaming, no network, network denied, data connection fail
Multiple PDN	Possibility to use different PDNs for multiple network access and services
Network protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DHCP, DNS, HTTP, HTTPS, SMTP, SSL v3, TLS, ARP, PPPoE, UPNP, SSH, Telnet, PPP, FTP, MQTT, Wake On Lan (WOL)
Networking features	NAT, Static/Dynamic routing, Firewall, OpenVPN, IPSec, H.232 and SIP-alg protocol NAT helpers, allowing proper routing of VoIP packets
Unique networking features	VLAN, Mobile quota control, WEB Filter, Load Balancing, Network Backup, Auto Failover
Connection monitoring	Ping Reboot, Periodic Reboot, LCP and ICMP for link inspection
Authentication	Pre-shared key, digital certificates, X.509 certificates
Keep settings	Update FW without loosing current configuration
Monitoring & Management	WEB UI, SSH, SMS, SNMP, JSON-RPC, FOTA, RMS
Supported languages	Busy box shell, Lua, C, C++
Development tools	SDK package with build environment provided

For More Information, please contact

AUTOMATION SYSTEMS & SOULTION

T - 12, 3rd Floor, Pankaj Central Market, I. P. Extn., Patparganj, Delhi - 110092

Phone: +91 11 41709077 / 22232187 **E - Mail**: infoautomation18@gmail. com